



NeoHybridPositiveDisplacementBailer Systems
General Preparation & Run-in Procedures
(NeoHybridPDB Systems)


Document # DRI-0118-0250

NeoHybridPDB Systems are non-explosive **Positive Displacement Bailer Systems** used to place **NeoSuperSlurry** atop platforms in wellbores.

NeoHybridPDBs are available in **1 3/4", 2", 2 1/8", 2 1/2", 3", 3 1/2", 4" & 5"** run-in diameters.

PURGE ALL GAS FROM THE INTERIOR OF THE NeoHybridDBA


1. Secure the **NeoHybridDBA** in a vise. Orient the DBA so that it is horizontal on a clean, flat surface. Remove the #2 Parker Plug (Item 22).
2. Verify that the resistance of the **NeoHybridDBA** is between 270 – 320 ohms. Contact **NeoProducts** if the **NeoHybridDBA** has resistance is out of this range or does not fire properly.
3. Make-up the Pump-in Fixture with the Fill Port on the Dual Valve Tandem Sub. Never wrap Teflon tape onto the threads of the Pump-In Fixture (Item 42) or the Pipe Plug (Item 26). Bits of Teflon tape can fowl the Check Valve and/or Solenoid Valve in the DBA.
4. Attach the Hydraulic Hand Pump to the Pump-In Fixture.
5. Keep the DBA oriented with the #2 Parker Plug Port facing upwards. Slowly pump hydraulic fluid into the DBA until hydraulic fluid is expelled from the #2 Parker Plug Port in the Electrical Contact Sub. Compressible air/gas has now been purged from the DBA.
6. Install the #2 Parker Plug (Item 22). Stand the DBA vertical upside down (the #2 Parker Plug Port will be near the ground). Continue to slowly pump hydraulic fluid until a steady stream of hydraulic fluid is expelled from the Weep Holes.
7. Make-up a "GO" Double Pin Electrical Sub to the DBA.
 - a. Check the resistance of the DBA. The resistance should be 270 – 320 ohms,
 - b. Connect a V_{dc} Power Supply to the DBA. Attach the positive lead to the "GO" Double Pin Electrical Contact Sub and the negative lead to the DBA body,

	2-1/2" NeoHybridPDB System Run-In Procedures	Date: 03/14/18	Page 1 of 7
		File Number: DRI-0118-0250	Rev. D

- c. Wrap a shop towel around the Dual Valve Tandem Sub (Item 6) where hydraulic fluid is discharged from the DBA. Approximately 2 fluid ounces of hydraulic fluid will be expelled upon DBA firing,
 - d. Slowly increase the current over 3 – 4 seconds to 450-500 milliamps,
 - e. Proper DBA firing is demonstrated by expelling hydraulic fluid into the shop towel,
 - f. Record the threshold current and voltage needed to fire the DBA.
8. Slowly pump hydraulic fluid into the NeoHybridDBA until a steady stream of hydraulic fluid is expelled from the Weep Holes.
 9. Make-up the NeoHybridDBA to the NeoCockingTool. The pressure required to cock the DBA is approximately 85 psig. Attach a water supply to the inlet manifold of the 2-1/2" NeoCockingTool (P/N 0118-250-011).
 10. Once the water supply is attached, open all valves on the NeoCockingTool. Purge all air out of the system. Close all valves.
 11. Slowly open the inlet valve and allow the water supply to stroke the NeoCockingTool. The NeoCockingTool will move the Swab Piston upward while simultaneously compressing the Springs (Item 34). You will see (thru the vent holes in the Spring Housing) and hear the springs rubbing against the Spring Housing as they compress. A 60 psig water supply will drive the cocking tool thru 90% of its cocking stroke. If the cocking tool stops stroking due to lack of pressure, the inlet valve can be closed. Compressed air can be used to complete the cocking operation. Do not allow the pressure in the NeoCockingTool to exceed 100 psig.
 12. When the NeoCockingTool approaches the top of its stroke a very small discharge of hydraulic fluid will be expelled from the Weep Holes. You will hear a distinctive "CLICK" come from the top section of the Spring Housing. The CLICK is the Collet Rod snapping into its service position. You will also see the top of the Swab Piston in the long oval holes at the bottom of the Swab Piston Housing.
 13. Close the inlet valve. Open the discharge valve. If the Swab Piston stays in place the DBA is "Locked & Loaded" and ready to be run in the hole.
 14. Close the discharge valve if the Swab Piston moves downward several inches. Repeat Steps #13 thru #16.
 15. Remove the Pump-in Fixture. Install the Pipe Plug.

MAKE-UP BAILER SYSTEM BHA


16. Make-up the "GO" Double Pin Electrical Sub with the CCL.
17. Place the NeoHybridDBA out of harm's way.
18. Obtain the NeoShearPistonAssembly (NeoSPA).
 - a. Disassemble the NeoSPA,

	2-1/2" NeoHybridPDB System Run-In Procedures	Date: 03/14/18	Page 2 of 7
		File Number: DRI-0118-0250	Rev. D

- b. Examine the O-Ring for service worthiness, replace as needed,
 - c. Apply downhole grease to the Shear Piston & O-Ring,
 - d. Firmly install the Shear Piston into the Bottom Fill Shear Sub,
 - e. Install a **Neo**ShearScrew to secure the Shear Piston in place,
 - f. Flip the Bottom Fill Shear Sub over and firmly tap the top of the Shear Piston hard enough to verify that the Shear Screw is in the shear groove,
 - g. Make-up the Bottom Fill Shear Sub with the Piston Cage and
 - h. Install the Bailer Cage Plug in the Piston Cage.
19. Obtain the Diameter O-Ring Sealed Bailer Joints to be used on the job. Inspect the bailers inside and out for service worthiness. Replace O-Rings as needed. Apply grease to the pins, boxes, and O-Rings.
20. Determine the amount of **Neo**SuperSlurry needed to fill the bailer. For example 40 ft of 2 1/2" Diameter Bailers will require 4 x 2.18 gallons per 10 ft joint = 8.72 gallons. Mix/prepare two (2) 5 gallon batches of **Neo**SuperSlurry.
21. If there is no mouse hole available go to Step #22. If the bailer can be lowered into a mouse hole or riser go to Step # 23.
22. Make-up the bailer string with the lubricator vertical or on the ground, for example;
- a. Make-up the bailer joints,

For the bailer joints, thread the pin end of one bailer joint into the box end of another by hand. Once the bailer joints are almost completely threaded, you may use a pipe wrench on each of the knurled sections to finish threading the two bailer joints into each other. Do not overtighten. If using a Bailer Clamp, attach the clamp to a knurled section of the bailer joints. Overtightening will result in damage to the bailer joints and possibly misruns.

- b. Make-up the **Neo**SPA with the bottom bailer joint,
- c. Make-up the **Neo**HybridDBA with the top bailer joint,
- d. Pull the BHA into the lubricator,
- e. Upright the lubricator,
- f. Lower the **Neo**SPA out the bottom of the lubricator,
- g. Make-up the **Neo**BottomFill System to the Bottom Fill Shear Sub,
- h. Place a gallon of fresh water in the **Neo**BottomFill Pail,
- i. Pump the water into the bailer. Do not allow the system to suck air into the bailer. Close the valve at the Bottom Fill Shear Sub before running out of water in the pail,
- j. Place 5 gallons of **Neo**SuperSlurry in the **Neo**BottomFill Pail,
- k. Open the valve and pump the slurry into the bailer,
- l. Regulate the pump rate so that the pump does not suck air,
- m. Keep adding slurry to the pail to keep the slurry height as high while bottom filling,
- n. Stop pumping slurry once water begins has gushed out the bottom of the **Neo**HybridDBA for a few seconds (You must make sure the system is

	2-1/2" NeoHybridPDB System Run-In Procedures	Date: 03/14/18	Page 3 of 7
		File Number: DRI-0118-0250	Rev. D

- completely filled with slurry and that there is no air in the system. Having any trapped air in the bailer can result in a misrun),
- o. Detach the bottom fill system,
- p. The bailer system is now ready to be pulled up into the lubricator and run into the well,
- q. Go to Step # 26.

23. Perform the following if a mouse hole or riser is available:

- a. Make-up the NeoSPA with a bailer joint,


For the bailer joints, thread the pin end of one bailer joint into the box end of another by hand. Once the bailer joints are almost completely threaded, you may use a pipe wrench on each of the knurled sections to finish threading the two bailer joints into each other. Do not overtighten. If using a Bailer Clamp, attach the clamp to a knurled section of the bailer joints. Overtightening will result in damage to the bailer joints and possibly misruns.

- b. Make-up the remainder of the bailer joints one joint at a time while lowering the NeoSPA one joint length at a time into the mouse hole,
- c. Attach a NeoBailerClamp below the top of the top bailer, hang off the bailer,
- d. Pour slurry into the bailer and verify that the top of slurry is 2 ft below the top of bailer joint,
- e. Remove the Swab Piston Housing from the bottom of the NeoHybridDBA,
- f. Make-up the Swab Piston Housing with the top bailer joint,
- g. Pour fresh water into the Swab Piston housing until water flows out of the oval holes in the housing, this will result in a 30" long water pad atop the 38' long slurry column,
- h. Make-up the NeoHybridDBA with the Swab Piston Housing (remember to re-install the locking Cap Screw (Item 18) at the top of the Housing),
- i. The bailer system is now ready to be pulled up into the lubricator and run into the well.


24. Perform all required safety and operational tasks and descend into the well.

- a. Locate the bottom of the bailer no greater than 1 – 3 ft above the platform upon which the slurry will be placed,
- b. Apply V_{dc} to the tool string, bring the current up to 450-500 mA and hold for 3 – 5 seconds,
- c. Remove the V_{dc} ,
- d. Repeat b & c, above, two more times (wait 60 seconds between each repeat),
- e. Pull out of the hole.

Note: Increased wireline length will affect line resistance. Additional voltage may need to be applied at surface to reach desired voltage at the tool head.


	2-1/2" NeoHybridPDB System Run-In Procedures	Date: 03/14/18	Page 4 of 7
		File Number: DRI-0118-0250	Rev. D

25. Once at the surface, lower the **NeoSPA** out the end of the lubricator, verify that the Shear Piston is located at the bottom of the Piston Cage.
26. Remove the **NeoSPA** from the bottom bailer joint.
 - a. Disassemble the **NeoSPA**,
 - b. Examine the O-Ring for service worthiness, replace as needed,
 - c. Clean the O-Ring & Shear Piston. Apply grease to the Shear Piston & O-Ring,
 - d. Firmly install the Shear Piston into the Bottom Fill Shear Sub,
 - e. Install a **NeoShearScrew** to secure the Shear Piston in place,
 - f. Flip the Bottom Fill Shear Sub over and firmly tap the top of the Shear Piston hard enough to verify that the Shear Screw is in the shear groove,
 - g. Make-up the Bottom Fill Shear Sub with the Piston Cage and
 - h. Make-up the **NeoSPA** with the bottom bailer joint.
27. If the bailer is run in brine that is heavier than 10.5 ppg or in crude oil or condensate, flush the bailer out with fresh water between every run in the hole using the **NeoBottomFill** System. Add an oil film breaking surfactant to the fresh water if the bailer is run thru oil or condensate.
28. If performing a job with the use of a mouse hole or riser, go to Step #29. If performing a job without the use of a mouse hole or riser perform the following:
 - a. Lay the bailer down and break the connection between the **NeoHybridDBA** and the top bailer joint,
 - b. With the DBA vertically upright. Remove the Pipe Plug (Item 26). Remove the #2 Parker Plug (Item 22). Install the Pump-in Fixture. Very slowly pump hydraulic fluid into the DBA until a steady flow of hydraulic fluid exits the DBA. The DBA is now thoroughly purged of gas,
 - c. Re-install the #2 Parker Plug,
 - d. Slowly pump hydraulic fluid into the DBA until a stream of hydraulic fluid is expelled from the both Weep Holes,
 - e. Wrap a shop towel around the Dual Valve Tandem Sub where the hydraulic fluid exits the DBA,
 - f. Fire the DBA by slowly increasing the current to 450-500 milliamps,
 - g. Upon "firing," the DBA will expel hydraulic fluid into the shop towel,
 - h. Record the threshold current and voltage needed to fire the DBA,
 - i. Continue on if the **NeoHybridDBA** fired properly,
 - j. Slowly pump hydraulic fluid into the **NeoHybridDBA** until a stream of hydraulic fluid is expelled from both Weep Holes.
 - k. Make-up the **NeoHybridDBA** to the **NeoCockingTool** and follow steps #9-15 to properly "cock" the DBA in the loaded position.
 - l. Make-up the bailer string with the lubricator vertical or on the ground, for example;
 - m. Make-up the **NeoHybridDBA** with the top bailer joint,
 - n. Pull the BHA into the lubricator,

	2-1/2" NeoHybridPDB System Run-In Procedures	Date: 03/14/18	Page 5 of 7
		File Number: DRI-0118-0250	Rev. D

- o. Upright the lubricator,
- p. Lower the NeoSPA out the end of the lubricator,
- q. Make-up the NeoBottomFill System to the Bottom Fill Shear Sub,
- r. Place ¾ of a gallon of fresh water in the NeoBottomFill Pail,
- s. Pump all the water into the bailer and close the ball valve at the Bottom Fill Shear Sub,
- t. Place 5 gallons of NeoSuperSlurry in the NeoBottomFill Pail,
- u. Open the ball valve and pump the slurry into the bailer,
- v. Regulate the pump rate so that the pump does not suck air,
- w. Keep adding slurry to the pail to keep the slurry height as high as possible while bottom filling,
- x. Stop pumping slurry once water begins to gush out the bottom of the NeoHybridDBA,
- y. The bailer system is now ready to be pulled up into the lubricator and run into the well.

29. Perform the following if a mouse hole or riser is available, otherwise go to Step #30:
- a. Attach a NeoBailerClamp 6” below the top of the top bailer, separate the NeoHybridDBA from the top bailer joint, hang off the bailer,
 - b. With the DBA vertically upright. Remove the Pipe Plug (Item 26). Remove the #2 Parker Plug. Install the Pump-in Fixture. Very slowly pump hydraulic fluid into the Pump-in Fixture until a steady flow of hydraulic fluid exits the DBA. The DBA is now thoroughly purged of gas,
 - c. Re-install the #2 Parker Plug,
 - d. Slowly pump hydraulic fluid into the NeoHybridDBA until a steady stream of hydraulic fluid is expelled from the Weep Holes,
 - e. Wrap a shop towel around the Dual Valve Tandem Sub where the hydraulic fluid exits the DBA,
 - f. Fire the DBA by slowly increasing the current to 450-500 milliamps
 - g. Upon “firing,” the DBA will expel hydraulic fluid into the shop towel,
 - h. Record the threshold current and voltage needed to fire the DBA,
 - i. Continue on if the DBA fired properly,
 - j. Slowly pump hydraulic fluid into the DBA until a stream of hydraulic fluid is expelled from both Weep Holes.
 - k. Remove the Pump-in Fixture and install the Pipe Plug.
 - l. Attach a water supply to the inlet manifold of the NeoCockingTool (P/N 0118-250-011). Make-up the NeoHybridDBA to the NeoCockingTool and follow steps #9-15 to properly “cock” the DBA in the loaded position
 - m. Pour slurry into the bailer and verify that the top of slurry is 2 ft below the top of the bailer joint,
 - n. Remove the Swab Piston Housing from the bottom of the NeoHybridDBA,
 - o. Make-up the Swab Piston Housing with the top bailer joint,
 - p. Pour fresh water into the Swab Piston housing until the water flows out of the oval holes in the housing, this will result in a 30”-long water pad atop of the 38’-long slurry column,


	2-1/2” NeoHybridPDB System Run-In Procedures	Date: 03/14/18	Page 6 of 7
		File Number: DRI-0118-0250	Rev. D

- q. Make-up the NeoHybridDBA with the Swab Piston Housing (remember to re-install the locking cap screw at the top of the housing, and
- r. The bailer system is now ready to be pulled up into the lubricator and run into the well.

- 30. Perform all required safety and operational tasks and descend into the well.
 - a. Locate the bottom of the bailer no greater than 1 – 3 ft above the platform upon which the slurry will be placed,
 - b. Apply V_{dc} to the tool string, bring the current up to 450-500 mA and hold for 3 – 5 seconds,
 - c. Remove the V_{dc} ,
 - d. Repeat b & c, above, two more times (wait 60 seconds between each repeat), and
 - e. Pull out of the hole.

Note: Increased wireline length will affect line resistance. Additional voltage may need to be applied at surface to reach desired voltage at the tool head.

- 31. Repeat Steps #25 thru #30 until the desired cement plug length is achieved.
- 32. Break down the BHA once bailing operations are complete. Examine the NeoHybridPDB components for general service worthiness. Contact NeoProducts if there appears to be any problems with the equipment or any need for product support.
- 33. Wipe down NeoProducts tools, fixtures, etc. Stow the equipment for;
 - a. Transportation to the shop for,
 - b. Disassembly, examination & redressing and/or rebuilding, and
 - c. Future service.

	2-1/2" NeoHybridPDB System Run-In Procedures	Date: 03/14/18	Page 7 of 7
		File Number: DRI-0118-0250	Rev. D