



The Elite Bridge Plug has proven to be a product that can be depended on. It has excellent running characteristics and secure sets. The plug can be set on different types of wireline pressure setting tools.

The Elite is designed for rapid drill-out while maintaining sufficient strength during the set. This plug sustains high pressures and temperatures.



## FEATURES

- Electric wireline set
- Drillable
- Cast iron construction
- One piece slips – hardened to depth of wicker only
- Sets in any grade casing including P-110
- Form-fitting metal back-ups prevent rubber extrusion
- For temporary or permanent service
- Ratcheting lock ring holds setting force

## SPECIFICATIONS

CASING		PLUG		SETTING RANGE		SETTING TOOL	
OD	WT. (LBS/FT)	PART NO.	O.D.	MIN.	MAX.	BAKER	GO
2 3/8	3.3 - 5.9	000-1710-002	1.71	1.867	2.107	05	
2 3/8	3.3-5.9	000-1710-000	1.71	1.867	2.107		1 11/16
2 7/8	6.4 - 6.5	000-2100-002	2.10	2.280	2.563	05	
2 7/8	6.4 - 6.5	000-2100-000	2.10	2.280	2.563		1 11/16
2 7/8	6.4 - 6.5	000-2100-000	2.10	2.280	2.563		2 1/8
3 1/2	5.7 - 10.2	000-2750-002	2.75	2.867	3.258	05	
3 1/2	5.7 - 10.2	000-2750-000	2.75	2.867	3.258	10	
3 1/2	5.7 - 10.2	000-2750-000	2.75	2.867	3.258		1 11/16
3 1/2	5.7 - 10.2	000-2750-000	2.75	2.867	3.258		2 1/8
3 1/2	12.7	000-2500-002	5.00	2.625	2.750	05	
3 1/2	12.7	000-2500-000	2.500	2.625	2.750		1 11/16
4	5.6 - 14	000-3120-002	3.12	3.340	3.732	10	2 1/8
4 1/2	9.5 - 16.6	000-3500-002	3.50	3.826	4.090	10	3 1/2
4 1/2	9.5 - 13.5	000-3710-002	3.71	3.920	4.560	10	3 1/2
5	11.5 - 21	000-3710-002	3.71	3.920	4.560	10	3 1/2
5 1/2	13 - 25	000-4240-002	4.24	4.580	5.047	20	3 1/2
5 3/4	22.5 - 25.2	000-4240-002	4.24	4.580	5.047	20	3 1/2
6	14 - 26	000-4750-002	4.75	5.140	5.595	20	3 1/2
6 5/8	34	000-4750-002	4.75	5.140	5.595	20	3 1/2
6	10.5 - 12	000-5340-002	5.34	5.595	6.366	20	3 1/2
6 5/8	17 - 34	000-5340-002	5.34	5.595	6.366	20	3 1/2
7	23 - 40	000-5340-002	5.34	5.595	6.366	20	3 1/2
6 5/8	17 - 22	000-5610-002	5.61	5.989	6.655	20	3 1/2
7	17 - 35	000-5610-002	5.61	5.989	6.655	20	3 1/2
7 5/8	20 - 39	000-6090-002	6.09	6.625	7.263	20	3 1/2
8 5/8	24 - 49	000-6960-002	6.96	7.511	8.248	20	3 1/2
9 5/8	29.3 - 53.5	000-7710-002	7.71	8.435	9.063	20	3 1/2
10 3/4	54 - 81	000-8710-002	8.71	9.250	9.784	20	3 1/2
10 3/4	32.7 - 51	000-9500-002	9.50	9.850	11.150	20	3 1/2
11 3/4	38 - 60	000-9500-002	9.50	9.850	11.150	20	3 1/2
13 3/8	77 - 102	000-1156-002	11.56	11.633	12.464	20	3 1/2
13 3/8	48 - 72	000-1200-002	12.00	12.347	12.715	20	3 1/2
16	65 - 109	000-1425-002	14.25	14.688	15.250	20	3 1/2
18 5/8	76 - 96.5	000-1725-002	17.25	17.655	18.730	20	3 1/2
20	133 - 169	000-1725-002	17.25	17.655	18.730	20	3 1/2