



The **Retrieveable Bridge Plug (RBP)** is a wireline set, wireline retrieved, packer-type bridge plug capable of holding differential pressure from above or below. The RBP is used as a temporary bridge plug for acidizing, fracturing, cementing, casing pressure tests, wellhead replacement, and zone isolation. The RBP utilizes standard wireline or hydraulic setting tools

SPECIAL FEATURES

- Wireline set/retrieve
- 10,000 PSI differential pressure rating **above and below the plug**
- Bi-directional slips
- Equalization feature prevents premature release against differential pressure
- Available in Nitrile, HSN, Viton, and Aflas.

Casing		Recommended Hole Size (inches)	Tool OD (inches)	Top Connection
Size (inches)	Weight (lbs/ft)			
3-1/2	7.7 - 10.2	2.922 - 3.068	2.700	5/8-18 UNF PIN
4	9.5 - 11.0	3.476 - 3.548	3.250	5/8-18 UNF PIN
	10.46 - 12.95	3.340 - 3.476	3.187	5/8-18 UNF PIN
4-1/2	9.5 - 13.5	3.920 - 4.090	3.750	1.000-8 UNC PIN
	13.5 - 15.1	3.826 - 3.920	3.650	1.000-8 UNC PIN
	15.1 - 16.6	3.754 - 3.826	3.625	1.000-8 UNC PIN
5	11.5 - 15.0	4.408 - 4.560	4.125	1.000-8 UNC PIN
	18.0 - 21.0	4.154 - 4.276	3.969	1.000-8 UNC PIN
5-1/2	13.0 - 20.0	4.778 - 5.156	4.625	7/8-14 UNF PIN
	20.0 - 23.0	4.670 - 4.778	4.500	7/8-14 UNF PIN
	23.0 - 26.0	4.548 - 4.670	4.375	7/8-14 UNF PIN
7	17.0 - 26.0	6.276 - 6.538	5.969	7/8-14 UNF PIN
	26.0 - 32.0	6.094 - 6.276	5.875	7/8-14 UNF PIN

