



**NeoFlex** Cement System  
Cefas Rated Gold  
P/N E0101-350-017-Cefas  
Service Range: 70° - 350° F (21° - 177° C)

### Availability

Class G and H Supersacks available for pumping jobs  
17 ppg • 5-gallon Batch Kits for bailing operations  
Dump Bailer Cement Kits are off-the-shelf ready-to-go cement kits

### Unique Physical Attributes

Ultra-low Permeability • Flexible • Post-Cure Expansion • High Shear Bond • Self-Healing

**NeoFlex** has unique physical properties that enhance fracture toughness, elasticity, bonding to casing and formations, and eliminates the occurrence of micro-cracking and gas migration.

**NeoFlex** is used to Block Gas Migration and the Occurrence of Sustained Casing Pressure (SCP)

### Applications

Rigless recompletions and well abandonments.

### Unique NeoFlex Features

- Post-cure expansion that seals and heals throughout well production life and abandonments,
- Blocks gas migration and eliminates the occurrence of SCP,
- Ultra-low permeability that prevents hydrocarbon migration,
- Flexibility and durability that eliminates the occurrence of micro-cracking, ensures long-term well integrity, and eliminates de-bonding between cement, casing, and formation.

**NeoProducts & HPI cement systems have been run in 100,000+ wells over the last 35 years.**

**NeoFlex plugs anchor, seal, heal and re-heal over a lifetime of well production & abandonment.**